

IN AFRICA FOR AFRICA



YUTONG D12

A renewed and chic exterior



Longer Life Cycle



Under normal driving conditions, vehicle main structure features a service life of 2 million km/20 years.

Safe and Worry-free Operation



700 MPa high-strength steel (three times stronger than standard steel) plus robust closed-ring structure ensure maximum passenger protection.

Large air intake grille, LED headlights, integrated light strips—dynamic yet elegant.

D12 SPECIFICATIONS







Item	Specifications			Version
L*W*H (mm)	12,000*2,600*3,820 (to roof hatch)/3,950(to AC)			-
Wheelbase, front/rear overhang (mm)	6,250, 2,265/3,485			-
Luggage compartment volume (m³)	14 (large)/13.5 (small)			-
Front/rear wheel tread (mm)	2,064/1,860			
Approach/departure angle (°)	13/13			
Complete vehicle curb weight (kg)	13,050 (400L/ without AC) 13,450 (400L/ with AC)			-
Front /rear axle (kg)	6,350/6,700 (400L/ without AC) 6,450/7,000 (400L/ with AC)			
Maximum manufacturer's total mass (kg)	18,500			
Front /rear axle (kg)	7,800/10,700			
Minimum turning diameter (mm)	≤24			
Maximum passenger capacity	68			
Fuel tank(L)	400			•
AC	No AC			•
	Kelin BFFS-06 dual system AC (32,000 kcal)			0
Tire	DOUBLE COIN: 315/80R22.5			•
	Michelin: 3315/80R22.5			0
Powertrain	Engine Model/ Emission/ Displacement (L)	Clutch	Transmission	
	L325 20/Euro II/8.9	Sachs MFZ430	Fast 6DSX150T	•
	L300 20/Euro II /8.9			0
	ISLe340 30/Euro III/8.88			0
Seat layout	55+1		•	
	66+1			0





66+1

55+1

"-"Not equipped, "●"Standard, "○"Optional

Yutong Bus Co., Ltd. Yutong Marketing Center, Economic and Technological Development Zone, Zhengzhou, China Tel: +86 371 6671 8999 Website: www.yutong.com E-mail: sales@yutong.com Follow us on Facebook & Twitter & YouTube at Yutong Bus & Coach