



## NEGATIVE PRESSURE AMBULANCE

ZK5038XJH Single protection

ZK5043XJH Dual protection



## Yutong's COVID-19 comprehensive mobility solution covers

Specimen collection - detection and diagnosis - transport and treatment - medical waste disposal - vaccination



Specimen collection



Detection and diagnosis



**Patient transport and treatment**



Medical waste disposal



Vaccination

## NEGATIVE PRESSURE AMBULANCE

This model is specially developed for the "transport and treatment" stage. It is a special ambulance product for transporting, treating and monitoring patients with infectious diseases, such as COVID-19.



### Single protection



### Dual protection



|  |   |
|--|---|
| <b>Safe and reliable</b>                   | Industry's favorite chassis: selected the chassis accounting for 80% in the ambulance platform industry, equipped with ABS safety system<br>Strong durability: Embedded electrophoretic coating, stainless for 10 years<br>Fire safety: Patient compartment uses fire-retardant materials<br>Water safety: Passed all-round high-pressure shower test |
| <b>Easy to use</b>                         | First aid within arm's reach:<br>All medical devices and drugs are within one arm's reach of medical practitioners  |
| <b>Double negative pressure protection</b> | Equipped with an additional negative pressure isolation compartment to quarantine the patient from the outside world during the whole process.  |

| Model configuration                             |                       |                       |
|---|-----------------------|-----------------------|
| Model   | ZK5043XJH             | ZK5038XJH             |
| Length*width*height (mm)                        | 4944*1972*2340        | 5380*1920*2480        |
| Interior height (mm)                            | 1600                  | 1600                  |
| Wheelbase (mm)                                  | 2835                  | 3100                  |
| Steering wheel                                  | Left rudder           | Left and right rudder |
| Motor model and emission standards              | JX493ZLQ5; Euro II, V | 4K22D4M; Euro II, V   |
| Fuel type                                       | Diesel                | Gasoline              |
| Displacement (L)                                | 2.77                  | 2.77                  |
| Rated capacity (person)                         | 7                     | 7                     |
| Maximum speed (km/h)                            | 120                   | 120                   |
| Interior trimming                               | Plate                 | Plate                 |
| Negative pressure ambulance-specific facilities |                       |                       |
| Medical equipment options                       |                       |                       |